

## DESOLDERING BRAID

### Advanced Braid Design

Our fine braid design has a strong capillary action that works instantly to pull solder. The large surface area created by the one-over, one-under construction enhances absorption and trapping of molten solder.

### Pure Materials

To ensure a quality and reliable product, we start with only the finest oxygen-free highly conductive (OFHC) fine gauge wire. Our 100% copper wick is then coated with flux, which cleans connections thoroughly during desoldering to ensure maximum solderability. This thin coating of flux also provides dependable, long-lasting protection from oxidation.

### Vacuum-Packaged

For longer shelf life before shipping, Techspray® vacuum seals ProWick® and No-Clean Desoldering Braid in durable clear plastic to protect from moisture and to prolong shelf life of the product. This special packaging ensures the highest possible quality from factory to production floor.



	#0 GREY	#1 WHITE	#2 YELLOW	#3 GREEN	#4 BLUE	#5 BROWN	#6 RED	BGA PURPLE	
<b>PROWICK® DESOLDERING BRAID (PURE ROSIN) BOBBINS</b>									
Size/Color	Längen: F=feet (0,3m)	1801	1802	1803	1804	1805	1806		
Product Availability	5F = 1,5 m 10F = 3 m 25F = 7,5 m 50F = 15 m	.035" [0.9mm]	.055" [1.4mm]	.075" [1.9mm]	.098" [2.5mm]	.130" [3.3mm]	.193" [4.9mm]		
Length	100F = 30 m 500F = 150 m	5F 10F 25F 50F 100F 500F	5F 10F 25F 50F 100F 500F	5F 10F 25F 50F 100F 500F	5F 10F 25F 50F 100F 500F	5F 10F 25F 50F 100F 500F	5F 25F 50F 100F 500F		
<b>PROWICK® DESOLDERING BRAID (PURE ROSIN) ANTI-STATIC BOBBINS</b>									
Size/Color		1826	1808	1809	1810	1811	1812	1813	1828
Product Availability		.025" [0.6mm]	.035" [0.9mm]	.055" [1.4mm]	.075" [1.9mm]	.098" [2.5mm]	.130" [3.3mm]	.193" [4.9mm]	.193" [4.9mm]
Length		5F 10F	5F 10F 25F 50F 100F	5F 10F 25F 50F 100F	5F 10F 25F 50F 100F	5F 10F 25F 50F 100F	5F 10F 25F 50F	5F 25F	5F
<b>NO-CLEAN DESOLDERING BRAID</b>									
Size/Color		1814	1815	1816	1817	1818	1819		
Product Availability		.035" [0.9mm]	.055" [1.4mm]	.075" [1.9mm]	.098" [2.5mm]	.130" [3.3mm]	.193" [4.9mm]		
Length		5F 10F 25F 50F 100F 500F	5F 10F 25F 50F 100F 500F	5F 10F 25F 50F 100F 500F	5F 10F 25F 50F 100F 500F	5F 10F 25F 50F 100F 500F	5F 25F 50F 100F 500F		
<b>NO-CLEAN DESOLDERING BRAID ANTI-STATIC BOBBINS</b>									
Size/Color		1827	1820	1821	1822	1823	1824	1825	1829
Product Availability		.025" [0.6mm]	.035" [0.9mm]	.055" [1.4mm]	.075" [1.9mm]	.098" [2.5mm]	.130" [3.3mm]	.193" [4.9mm]	.193" [4.9mm]
Length		5F 10F	5F 10F 25F 50F 100F	5F 10F 25F 50F 100F	5F 10F 25F 50F 100F	5F 10F 25F 50F 100F	5F 10F 25F 50F	5F 25F	5F
<b>UNFLUXED DESOLDERING BRAID ANTI-STATIC BOBBINS</b>									
Size/Color		1830	1831	1832	1833	1834	1835		
Product Availability		.035" [0.9mm]	.055" [1.4mm]	.075" [1.9mm]	.098" [2.5mm]	.130" [3.3mm]	.193" [4.9mm]		
Length		5F 10F	5F 10F	5F 10F	5F 10F	5F 10F	5F		

\* All dimensions are approximate. All products shipped in vacuum packaging.